

H K K 120 スーパーチェーン 伝動能力表

単位：Kw

小spro ケット歯数	小sproケット回転数 r.p.m												
	10	25	50	75	100	150	200	250	300	350	400	450	500
潤滑形式	A 2			B				C					
13	2.4	5.4	10.1	14.5	18.8	27.1	35.1	42.9	50.5	58.0	65.5	72.8	80.0
14	2.6	5.8	10.9	15.7	20.4	29.3	38.0	46.5	54.7	62.9	70.9	78.8	86.7
15	2.8	6.3	11.8	16.9	21.9	31.6	40.9	50.0	59.0	67.7	76.4	84.9	93.4
16	3.0	6.8	12.6	18.2	23.5	33.9	43.9	53.7	63.2	72.6	81.9	91.1	100.1
17	3.2	7.2	13.5	19.4	25.1	36.2	46.9	57.3	67.5	77.6	87.5	97.2	106.9
18	3.4	7.7	14.3	20.6	26.7	38.5	49.9	60.9	71.8	82.5	93.0	103.4	113.7
19	3.6	8.1	15.2	21.9	28.3	40.8	52.8	64.6	76.1	87.5	98.6	109.6	120.6
20	3.8	8.6	16.0	23.1	29.9	43.1	55.9	68.3	80.5	92.4	104.2	115.9	127.4
21	4.0	9.1	16.9	24.4	31.6	45.4	58.9	72.0	84.8	97.4	109.9	122.2	134.3
22	4.2	9.5	17.8	25.6	33.2	47.8	61.9	75.7	89.2	102.5	115.5	128.5	141.2
24	4.6	10.5	19.5	28.1	36.4	52.5	68.0	83.1	98.0	112.5	126.9	141.1	155.2
26	5.0	11.4	21.3	30.7	39.7	57.2	74.2	90.7	106.8	122.7	138.4	153.9	169.2
30	5.8	13.3	24.9	35.8	46.4	66.8	86.6	105.8	124.7	143.2	161.5	179.6	197.4
32	6.3	14.3	26.6	38.4	49.7	71.6	92.8	113.4	133.7	153.6	173.2	192.5	211.7
35	6.9	15.7	29.4	42.3	54.8	78.9	102.2	125.0	147.2	169.2	190.8	212.1	233.2
40	8.0	18.2	33.9	48.8	63.3	91.2	118.1	144.4	170.1	195.4	220.4	245.0	269.4