

H K K 160 スーパーチェーン 伝動能力表

単位：Kw

小spro ケット歯数	小sproケット回転数 r.p.m												
	10	25	50	75	100	150	200	250	300	350	400	450	500
潤滑形式	A 2			B				C					
13	4.7	6.8	10.8	16.5	20.2	30.8	37.7	54.2	70.3	85.9	101.2	116.3	131.1
14	5.1	7.4	11.7	17.9	21.9	33.4	40.8	58.8	76.1	93.1	109.7	126.0	142.1
15	5.5	8.0	12.6	19.3	23.6	36.0	44.0	63.3	82.0	100.3	118.1	135.7	153.0
16	5.9	8.5	13.5	20.7	25.3	38.5	47.1	67.9	87.9	107.5	126.7	145.5	164.1
17	6.3	9.1	14.4	22.1	27.0	41.2	50.3	72.5	93.9	114.8	135.2	155.4	175.2
18	6.7	9.7	15.4	23.5	28.7	43.8	53.5	77.1	99.9	122.1	143.8	165.3	186.4
19	7.1	10.3	16.3	24.9	30.4	46.4	56.7	81.7	105.9	129.4	152.5	175.2	197.6
20	7.5	10.9	17.2	26.3	32.1	49.1	60.0	86.4	111.9	136.8	161.2	185.2	208.8
21	8.0	11.5	18.2	27.7	33.9	51.7	63.2	91.0	118.0	144.2	169.9	195.2	220.1
22	8.4	12.1	19.1	29.1	35.6	54.4	66.5	95.7	124.0	151.6	178.7	205.2	231.5
24	9.2	13.2	21.0	32.0	39.1	59.7	73.0	105.2	136.3	166.6	196.3	225.5	254.3
26	10.0	14.4	22.9	34.9	42.7	65.1	79.6	114.7	148.6	181.6	214.0	245.8	277.2
30	11.7	16.8	26.7	40.7	49.8	76.0	92.9	133.8	173.4	211.9	249.7	286.9	323.5
32	12.5	18.1	28.6	43.7	53.4	81.5	99.6	143.5	185.9	227.2	267.8	307.6	346.9
35	13.8	19.9	31.5	48.1	58.8	89.8	109.7	158.1	204.8	250.3	295.0	338.9	382.2
40	16.0	23.0	36.4	55.6	67.9	103.7	126.8	182.6	236.6	289.2	340.7	391.4	441.4