

HKK80スーパーチェーン 伝動能力表

単位：Kw

小spro ケット歯数	小sproケット回転数 r.p.m												
	10	25	50	100	150	200	250	300	350	400	500	600	700
潤滑形式	A 2			B							C		
13	0.9	2.1	3.9	7.2	10.4	13.4	16.4	19.3	22.2	25.1	30.6	36.1	32.1
14	1.0	2.2	4.2	7.8	11.2	14.5	17.8	21.0	24.1	27.1	33.2	39.1	35.9
15	1.1	2.4	4.5	8.4	12.1	15.7	19.2	22.6	25.9	29.2	35.7	42.1	39.8
16	1.1	2.6	4.8	9.0	13.0	16.8	20.5	24.2	27.8	31.4	38.3	45.2	51.9
17	1.2	2.8	5.2	9.6	13.8	17.9	21.9	25.8	29.7	33.5	40.9	48.2	55.4
18	1.3	2.9	5.5	10.2	14.7	19.1	23.3	27.5	31.6	35.6	43.5	51.3	58.9
19	1.4	3.1	5.8	10.8	15.6	20.2	24.7	29.1	33.5	37.7	46.1	54.4	62.5
20	1.4	3.3	6.1	11.5	16.5	21.4	26.1	30.8	35.4	39.9	48.8	57.5	66.0
21	1.5	3.5	6.5	12.1	17.4	22.5	27.5	32.5	37.3	42.1	51.4	60.6	69.6
22	1.6	3.6	6.8	12.7	18.3	23.7	29.0	34.1	39.2	44.2	54.1	63.7	73.2
24	1.8	4.0	7.5	14.0	20.1	26.0	31.8	37.5	43.1	48.6	59.4	70.0	80.4
26	1.9	4.4	8.2	15.2	21.9	28.4	34.7	40.9	47.0	53.0	64.7	76.3	87.6
30	2.2	5.1	9.5	17.8	25.6	33.1	40.5	47.7	54.8	61.8	75.6	89.0	102.3
32	2.4	5.5	10.2	19.0	27.4	35.5	43.4	51.2	58.8	66.3	81.0	95.5	109.7
35	2.6	6.0	11.2	21.0	30.2	39.1	47.8	56.4	64.7	73.0	89.3	105.2	120.8
40	3.0	7.0	13.0	24.2	34.9	45.2	55.2	65.1	74.8	84.3	103.1	121.5	139.6